

Valves and Quick Couplers Valves and Fittings

Quick Coupler Shut-Off Fittings

Use with existing charging hose. Immediately traps refrigerant discharge from hose when disconnected from access fitting. For use with Kobra™ hoses only

| | The second second | | |
|--------|------------------------|--|--|
| 33112N | 1/4" QC x 1/4" SAE | | |
| 33113N | 1/4" QC x 1/4" SAE 90° | | |

Replacement Parts

| | CONTRACTOR OF THE PROPERTY OF |
|--------|---|
| | |
| P90022 | O-Ring |





1/4" Core Depressor

| | Testaription |
|--------|--------------------------------|
| A33500 | 1/4" thumbscrew core depressor |



Quick Coupler Access Tee

O-Ring seal quick coupler. Furnishedd with cap and valve core

| | Pesylphen | |
|--------|-------------------------------------|----|
| A34000 | 1/4" QC x 1/4" access branch tee | 15 |
| P90009 | Replacement O-Ring | |

Swivel Cylinder Valve

Finger tight seal. Includes gasket

| | Description |
|----------|-------------------------|
| CV-20004 | 3/4" NPS x 1/4" M flare |
| CV-20006 | 3/4" NPS x 3/8" M flare |




Back Seating Control Valve

Ideal for use on precharged line sets. Eliminates spraying of leak detection dye and refrigerant. Compact brass body for long service. Swivel coupler with double safety grooves.

Replacement Parts

| | Description | | Događe |
|--------|--------------------------------------|--------|--------|
| A33000 | 1/4" SAE x 1/4" O-ring quick coupler | P90009 | O-Ring |



Quick Couplers

1/4" and 5/16"3/8" couplers with pattened O-Ring seal or deep vacuum. No depressor.

1/4" and 5/16" couplers with valve core depressor, safety channels and rubber gasket seal

3/16" couplers with valve core depressor, safety channels and O-Ring seal

For 410A 5/16" connections, use QC-S5

Elbow

| EIDOW | | Straight | | |
|--------|---------------------------------|---------------|---------|--------------------------------------|
| | Description | | |). Peremption |
| QC-E3 | 3/16" QC X 1/ | 4" SAE elbow | QC-S3 | 3/16" QC X 1/4" SAE |
| QC-E4 | 1/4" QC X 1/4 | " SAE elbow | QC-S4 | 1/4" QC X 1/4" SAE |
| QC-E5 | 5/16" QC X 1/ | '4" SAE elbow | QC-S46 | 1/4" QC X 3/8" SAE |
| QC-E64 | 3/8" QC X 1/4 (no depressor) | " SAE elbow | QC-S5 | 5/16" QC X 1/4" SAE |
| allay. | (no depressor) | N. Salling | QC-S64 | 3/8" QC X 1/4" SAE (no depressor) |
| O. | 0 | 0 | QC-\$65 | 3/8" QC X 5/16" SAE (no depressor) |
| QC-E3 | QC-S3 | QC-S4A | | (, |

FPT Thread

| | Barrier III |
|--------|--------------------|
| QC-S4A | 1/4" QC X 1/8" FPT |
| QC-S4B | 1/4" QC X 1/4" FPT |

Replacement Parts

| P90009 | 3/16" O-Ring | |
|--------|-----------------------|--|
| P509 | 1/4" gasket | |
| P90513 | Depressor for 1/4" QC | |
| P90012 | 3/8 O-Ring | |