



<b>DAYAN</b>	<b>Customer</b>
<b>VERTICAL LIQUID RECEIVER</b>	<b>Product</b>
<b>V6A.60B.14.BH4.BH4.FH4.H31</b>	<b>Code</b>
	<b>Customer Code</b>

TECHNICAL INFORMATION	
Fluid Group	2
Cooler Fluid Type	HCFC-HFC-CFC
Desing Calculation	EN 14276-1/EN 13445-3
Welded Joint Efficiency	0.85
Material Group (Shell / Head)	1.1 / 1.2
Testing Group	3b
Ndt	ACC. TO EN 13445
Capacity [Lt.]	14 Lt.
Operating Pressure [PS]	60 Bar
Pneumatic Test Pressure [PT]	86 Bar
Allowable Temperature [TS]	Min.-10C / Max.+100C
Category	CAT II / A2
Packaging Size & Weight	00*00*00 & 00 Kg.
Drawed By	C.ISIK
Approved By	Ö.TOKUR
Date	09.12.2020
Revision Date	00.00.0000

NO	CONNECTION	MODEL	QTY
01	Inlet Connection	ODS 5/8"	1 Pcs.
02	Inlet - Valve		
03	Outlet Connection	ODS 5/8"	1 Pcs.
04	Outlet - Valve		
05	Safety Valve Connection	NPT 1/2"	1 Pcs.
06	Blind Plug Fitting for SV	NPTF 1/2"	1 Pcs.
07	Safety Valve		
08	Sight Glass Connection	SW38 Conn.	2 Pcs.
09	Sight Glass Type	SW38	2 Pcs.
10	Level Sensor Connection		
11	Level Sensor Plug		
12	Level Sensor		
13	Extra Connection		
14	Color		RAL 9005