

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

SECTION 1. IDENTIFICATION

Product name : Genetron® 507 (R-507)

Number : 000000009882

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell Trading (Shanghai) Co., Ltd.
No.69 Xi Ya Rd,
Shanghai, 020 200131

For more information call : 800-522-8001
+1-973-455-6300(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: Transportation (CHEMTREC): 1-800-424-9300 or
+1-703-527-3887
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : very faint sweet

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Storage:**
Protect from sunlight. Store in a well-ventilated place.Hazards not otherwise
classified: May cause frostbite.
May cause cardiac arrhythmia.
May cause eye and skin irritation.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

: Mixture of 1,1,1-Trifluoroethane and Pentafluoroethane

Chemical nature

: Mixture

Chemical name	CAS-No.	Concentration
Pentafluoroethane	354-33-6	50.00 %
1,1,1-Trifluoroethane	420-46-2	50.00 %

SECTION 4. FIRST AID MEASURES

General advice

: First aider needs to protect himself. Move out of dangerous

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

- area. Take off all contaminated clothing immediately.
- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Indication of immediate medical attention and special treatment needed, if necessary : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : The product is not flammable.
ASTM E-681
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during firefighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

Do not allow run-off from fire fighting to enter drains or water courses.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Rapid evaporation of the liquid may cause frostbite.

Fire may cause evolution of:

Halogenated compounds

Hydrogen fluoride

Carbon oxides

Carbonyl halides

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Methods and materials for containment and cleaning up : Ventilate the area.

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

Storage

Conditions for safe storage, including any incompatibilities : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapor.
Avoid contact with skin, eyes and clothing.

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Engineering measures : General room ventilation is adequate for storage and handling. Perform filling operations only at stations with exhaust ventilation facilities.
- Eye protection : Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/ face shield/ eye protection.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Pentafluoroethane	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.

SAFETY DATA SHEET

Honeywell**Genetron® 507 (R-507)****10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

Pentafluoroethane	354-33-6	TWA : Time weighted average	4,900 mg/m3 (1,000 ppm)	2020	WEEL:US Workplace Environmental Exposure Level
1,1,1-Trifluoroethane	420-46-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1-Trifluoroethane	420-46-2	TWA : Time weighted average	3,400 mg/m3 (1,000 ppm)	2020	WEEL:US Workplace Environmental Exposure Level
1,1,1-Trifluoroethane	420-46-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1-Trifluoroethane	420-46-2	TWA : Time weighted average	3,400 mg/m3 (1,000 ppm)	2020	WEEL:US Workplace Environmental Exposure Level
Pentafluoroethane	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
Pentafluoroethane	354-33-6	TWA : Time weighted average	4,900 mg/m3 (1,000 ppm)	2020	WEEL:US Workplace Environmental Exposure Level

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquefied gas
Color	: colourless
Odor	: very faint sweet
Odor threshold	: Note: No data available
pH	: Note: neutral
Freezing point	: Note: not determined
Boiling point/boiling range	: -46.7 °C
Flash point	: Note: Not applicable
Evaporation rate	: > 1 Method: Compared to CCl4.
Lower explosion limit	: Method: ASTM E-681 Note: None
Upper explosion limit	: Method: ASTM E-681 Note: None
Vapor pressure	: 10,611 hPa at 21.1 °C(70.0 °F) 25,289 hPa at 54.4 °C(129.9 °F)
Vapor density	: 3.43 Note: (Air = 1.0)
Density	: 1.07 g/cm ³ at 21.1 °C

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

Water solubility	:	1.5 g/l
Partition coefficient: n-octanol/water	:	log Pow: 1.48 Test substance: Ethane, pentafluoro- (HFC-125)
Ignition temperature	:	> 750 °C
Decomposition temperature	:	> 250 °C Note: To avoid thermal decomposition, do not overheat.
Viscosity, dynamic	:	Note: No data available
Viscosity, kinematic	:	Note: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials	:	Oxidizing agents Finely divided metal powders such as aluminum, magnesium, or zinc.

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

Hazardous decomposition products : Halogenated compounds
Hydrogen fluoride
Carbonyl halides
Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

Pentafluoroethane : > 769000 ppm
Exposure time: 4 h
Species: Rat

1,1,1-Trifluoroethane : LC50: > 540000 ppm
Exposure time: 4 h
Species: Rat

LC50: > 106 mg/l
Exposure time: 4 h
Species: Rat

Sensitisation

Pentafluoroethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
75 000 ppm
Lowest observed effect level
100 000 ppm

1,1,1-Trifluoroethane : Cardiac sensitization
Species: dogs
Note: 1,1,1,2-tetrafluoroethane (HFC-134a): Cardiac sensitisation threshold (dog): 80000 ppm.

Repeated dose toxicity

Pentafluoroethane : Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOEL: 50000 ppm

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

	Subchronic toxicity
1,1,1-Trifluoroethane	: Species: Rat Application Route: Inhalation Exposure time: (90 d) NOEL: 40000 ppm Subchronic toxicity
Genotoxicity in vitro Pentafluoroethane	: Test Method: Ames test Result: negative
1,1,1-Trifluoroethane	: Test Method: Ames test Result: negative
	: Cell type: Human lymphocytes Result: negative
	: Cell type: Chinese Hamster Ovary Cells Result: negative
	: Cell type: Human lymphocytes Result: negative
Genotoxicity in vivo 1,1,1-Trifluoroethane	: Species: Mouse Cell type: Bone marrow Application Route: Inhalation Result: negative
Teratogenicity Pentafluoroethane	: Species: Rabbit Application Route: Inhalation exposure NOAEL, Teratog: 50,000 ppm NOAEL, Maternal: 50,000 ppm Note: Did not show teratogenic effects in animal experiments.
	Species: Rat Application Route: Inhalation exposure NOAEL, Teratog: 50,000 ppm NOAEL, Maternal: 50,000 ppm

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

- Note: Did not show teratogenic effects in animal experiments.
- 1,1,1-Trifluoroethane : Species: Rat
Application Route: Inhalation exposure
NOAEL, Teratog: 40,000 ppm
NOAEL, Maternal: 40,000 ppm
Note: Did not show teratogenic effects in animal experiments.
- Species: Rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 40,000 ppm
NOAEL, Maternal: 40,000 ppm
Note: Did not show teratogenic effects in animal experiments.
- Further information : Acute toxicity Ethane, pentafluoro- (HFC-125): Cardiac sensitisation threshold (dog): 75000 ppm. 1,1,1-trifluoroethane (HFC-143a): Cardiac sensitisation threshold (dog): >250000 ppm. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. Irritating to eyes and skin. Avoid skin contact with leaking liquid (danger of frostbite). May cause cardiac arrhythmia.

SECTION 12. ECOLOGICAL INFORMATION

- Biodegradability
Pentafluoroethane : Result: Not readily biodegradable.
Value: 5 %
Method: OECD 301 D

Further information on ecology

- Additional ecological information : Accumulation in aquatic organisms is unlikely. This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

Note : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163
 Proper shipping name : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, 1,1,1-Trifluoroethane)
 Class : 2.2
 Packing group :
 Hazard Labels : 2.2

IATA UN/ID No. : UN 3163
 Description of the goods : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, 1,1,1-Trifluoroethane)
 Class : 2.2
 Hazard Labels : 2.2
 Packing instruction (cargo aircraft) : 200
 Packing instruction (passenger aircraft) : 200

IMDG UN/ID No. : UN 3163
 Description of the goods : LIQUEFIED GAS, N.O.S.
 (PENTAFLUOROETHANE,
 1,1,1-TRIFLUOROETHANE)
 Class : 2.2
 Hazard Labels : 2.2
 EmS Number : F-C, S-V
 Marine pollutant : no
 IMDG Code segregation group according chapter 3.1.4.4 : NONE,

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

SECTION 15. REGULATORY INFORMATION**Inventories**

USA. List of Active Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended : On TSCA Inventory

Australia. Inventory of Industrial Chemicals (AIIC), as amended : On the inventory, or in compliance with the inventory

Canada. Domestic Substances List (DSL), as amended : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS) : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC) : On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI) : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Genetron® 507 (R-507)**10639906**

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

- SARA 313 Components** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
- SARA 311/312 Hazards** : Acute Health Hazard
Sudden Release of Pressure Hazard
- California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous

Genetron® 507 (R-507)

10639906

Version 2.8

Revision Date 03/21/2024

Print Date 05/16/2024

versions.

Previous Issue Date: 05/08/2019

Prepared by Honeywell Energy and Sustainability Solutions Product Stewardship Group Product Stewardship Group